

Erro Pendant

AC1134, AC1144, AC1158 | 1.0

GENERATION LIGHTING PENDANTS

GENERAL PRODUCT INFORMATION:


These fixtures are intended to be installed utilizing NEC compliant junction boxes.

This product is safety listed for damp locations.

This instruction shows a typical installation.

CAUTION - RISK OF FIRE
This product must be installed in accordance with the applicable installation code by a person familiar with the construction and operation of the product and the hazards involved.
Use minimum 90°C supply conductors.


SAVE THESE INSTRUCTIONS!



GENERATION LIGHTING
7400 Linder Ave., Skokie, IL 60077
T 847.410.4400 | F 847.410.4500
www.generationlighting.com

Install the Fixture

IA



- 1** Assemble the frames by installing the corners using the corner screws.
- 2** Install the glass to the frames facing the proper direction using the frame screws. Install the felt pads where shown.
- 3** If necessary, screw the short end of the threaded nipple tightly onto the mounting plate, then screw the screw collar and canopy loop onto the threaded nipple.
- 4** Secure the mounting plate to the junction box.
- 5** Determine the wanted height of the fixture and remove a portion of the chain from the bottom by opening a link with pliers.
- 6** Feed the cord through the pipe and screw it onto the socket assembly, then place the support onto the pipe.
- 7** Lower the frame onto the support and secure them together using the frame screws.
- 8** Feed the cord through the fixture loop, then screw the fixture loop onto the pipe.
- 9** Install a quick link to bottom end of the chain, then secure the link onto the fixture loop.
- 10** Unscrew the collar nut from the screw collar, then install the collar nut and the canopy onto the chain (in that order).
- 11** Install a quick link onto the remaining end of the chain, then secure the quick link onto the canopy loop.
- 12** Weave the cord through the chain, canopy loop, and canopy, threaded nipple, and out of the junction box. Trim the cord leaving enough to make electrical connections.
- 13** Connect the fixture to a suitable ground in accordance to local electrical codes.
- 14** Connect the white fixture wire (square and/or rigid) to the neutral power line wire with a wire nut.
- 15** Connect the black fixture wire (round and/or smooth) to the hot power line wire with a wire nut.
- 16** Neatly place all the wires into the junction box, place the canopy onto the mounting plate, and secure it in place by screwing the collar nut tightly onto the screw collar followed by screwing the canopy loop onto the threaded nipple.
- 17** Install the candle tubes by sliding them over the sockets.
- 18** Screw the lamps into the sockets. Refer to the label on the lamp socket for Max Wattage information.